

## Network Camera Firmware

Version: V5.5.73

Release Note (**External**)

(2019-06-15)

Firmware Basic Information	Firmware Version: V5.5.73_190520
----------------------------------	----------------------------------

### 6 Series Camera Firmware V5.5.73 build190520 Features

#### 1. Optimization

- Newly add 4PTZ Fusion display mode under Hardware decoding mode.
- Newly add Cylinder display mode under Software decoding when adopting Ceiling mount and Table mount.
- Support send report of Heat Map, Intersection Analysis and People counting via email.
- Newly support draw shield region for Heat Map, up to 4 regions.
- Newly add 720\*480 resolution of sub-stream for DS-2CD6365G0.
- Newly add 640\*480 resolution of sub-stream for DS-2CD63C5G0.
- Support draw polygon of detection area.
- Newly support People Counting function.
- Speaker is disabled by default and it is necessary to enable two-way audio firstly.

## Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action.

For any questions and request for this firmware, please contact our local technical support team.

### **Remarks:**

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.  
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,  
China  
Tel: +86-571-8807-5998  
FAX: +86-571-8993-5635  
Email: [overseabusiness@hikvision.com](mailto:overseabusiness@hikvision.com)

## Supported Product List (63X5)

Product Category	Model Number	Product Description
Fisheye Camera	DS-2CD6365G0-I(V)(S)	6MP, Heat map, 120dB WDR
Fisheye Camera	DS-2CD63C5G0-I(V)(S)	12MP, Heat map, DWDR
Fisheye Camera	DS-2CD6365G0E-I(V)(S) (B)	6MP, Dual-Mic
Fisheye Camera	DS-2CD63C5G0E-I(V)(S) (B)	12MP, Dual-Mic
Fisheye Camera	DS-2CD6365G0E-(S)/RC	6MP, In-ceiling Mounting
Fisheye Camera	DS-2CD63C5G0E-(S)/RC	12MP, In-ceiling Mounting
Fisheye Camera	DS-2XM6365G0-IV(S)	6MP, Dual-Mic
Fisheye Camera	DS-2XM6365G0-IVM/(ND)	6MP, M12, PoE
Fisheye Camera	DS-2XM63C5G0-IV(S)	12MP, Dual-Mic
Fisheye Camera	DS-2XM63C5G0-IVM(ND)	12MP, M12, PoE